



EXPERIENCE REPUTABLE PROCESS

## Liqufied Petroleum Gas (LPG) specification

Refrigerated propane (C3) properties

Supplier 1

Properties	Test Method	Value	Units
Ethane	GC.	0.4 Max	Mol %
Propane	GC.	98 Min	Mol %
Butane	GC.	1.4 Max	Mol %
Butane & Heavier	GC.	0.01 Max	Mol %
Copper Corrosion	D-1838	NO. 1a Max	--
Hydrogen Sulfide	D-2420	5 Max	Vol.ppm
Vapor Pressure	D-2598	200 Max	200 Max
Water Content	D-2713	Pass	--



EXPERIENCE REPUTABLE PROCESS

## Liqified Petroleum Gas (LPG) specification

Refrigerated Butane (C4) properties

Supplier 1

Properties	Test Method	Value	Units
Ethane	GC.	0.08 Max	Mol %
Propane	GC.	2 Max	Mol %
Total-C4	GC.	97.5 Max	Mol %
Total-C5	GC.	0.082 Max	Mol %
Copper Corrosion	D-1838	NO. 1a Max	--
Total Sulfur	D-3246	30 Max	Wt.ppm
Hydrogen Sulfide	D-2420	5 Max	Vol.ppm
Vapor Pressure @ 100 °F	D-2598	70 Max	200 Max
Water Content	SHAW DEW POINT	Pass	--