



EXPERIENCE REPUTABLE PROCESS

Diesel specification

Supplier 1

NO.	Analysis	Unit	Limit	Test Method
1	Distillation	-----	-----	ASTM D86
2	Recovered@ 150°C	%VOL	report	ASTM D86
3	Recovered @300°C	%VOL	report	ASTM D86
4	Recovered @ 357- °C (min)	%VOL	90	ASTM D86
5	F.B.P. (max)	°C	385	ASTM D86
6	Densiby @ 15°C	Kg/m ³	820-860	ASTM D1298
7	Color (max)	-----	3	ASTM D1500
8	Corrosion 3hr @100°C	-----	1a	ASTM D130
9	Flash point (min)	°C	Report	ASTM D93
10	Sulphur Total (max)	wt%	1	ASTM D1552
11	Viscosity kinematic @37.8°C	c.st	2.0 - 5.5	ASTM D445



EXPERIENCE REPUTABLE PROCESS

12	Cloud point (max)	°C	2.0* *	ASTM D2500
13	Pour point (max)	°C	-3* *	ASTM D97
14	Carbon residue on 10%- Bottoms(max)	wt%	0.1	ASTM D189
15	Ash (max)	wt%	0.01	ASTM D482
16	Water & sediment (max)	%VOL	0.05	ASTM D2709
17	Cetane index (min)	50	ASTM D976

TIDOTS OIL

TIDOTS OIL