



EXPERIENCE REPUTABLE PROCESS

Base oil solvent specification

White Spirit (AW-402) Specification

Supplier 1

No.	Item	Result	Test method
item	Sp.Gr at 15.6 °C	Min 0.7775	D-1298
1	IBP (°C)	142-158	ASTM D-86
2	10 % (°C)	Min 158	
3	50 % (°C)	Max 179	
4	90 % (°C)	Max 194	
5	Dry Point (°C)	Max 198	
6	F.B.P (°C)	-	
7	Flash Point (°C)	42-47	D-93
8	Total Sulfur (ppm)	Max 500	D-2622/4294
9	Aromatic (Vol %)	Max 20	D-6839/1319

TIDOTS OIL



EXPERIENCE REPUTABLE PROCESS

Base oil solvent specification

Technical specification of Es-502

Supplier 1

NO.	Item	Result	Test method
1	Sp.Gr at 15.6 °C	Min 0.8120	D-1298
2	IBP (°C)	180-185	ASTM D-86
3	10 % (°C)	198	
4	50 % (°C)	206	
5	90 % (°C)	Max 240	
6	Dry Point (°C)	Max 198	
7	F.B.P (°C)	Max 250	
8	Flash Point (°C)	40-46	D-93
9	Total Sulfur (ppm)	Max 50	D-2622/4294
10	Aromatic (Vol %)	17	D-6839/1319



EXPERIENCE REPUTABLE PROCESS

Base oil solvent specification

Technical specification of Es-503:

Supplier 1

No.	Item	Result	Test method
1	Sp.Gr at 15.6 °C	Min 0.8290	D-1298
2	IBP (°C)	210 - 218	ASTM D-86
3	10 % (°C)	243	
4	50 % (°C)	247	
5	90 % (°C)	251-255	
6	Dry Point (°C)	-	
7	F.B.P (°C)	270-295	
8	Flash Point (°C)	55 Min	D-93
9	Total Sulfur (ppm)	Max 6000	D-2622/4294
10	Aromatic (Vol %)	20	D-6839/1319